

# AUTOMATIC SPRINKLERS

## STANDARD SPRAY SPRINKLERS

### RFII "ROYAL FLUSH II"

#### Pendent Concealed

- Light hazard/Ordinary hazard
- 5 mm bulb (standard)  
3 mm bulb (quick)
- Concealed in an enclosed escutcheon plate with flat cover for use in those applications where aesthetics is a primary consideration
- Separable, two-piece design of the mounting cup and cover plate allows installation of the sprinklers and pressure testing of the fire protection system prior to installation of a suspended ceiling or application of the finish coating to a fixed ceiling
- Internally threaded closure with  $\frac{1}{2}$ " (12,7 mm) of adjustment
- Available with optional dust and air seal

|                           |   |
|---------------------------|---|
| <b>K FACTOR</b>           | K=5.6 (80,6)  |
| <b>THREAD SIZE</b>        | $\frac{1}{2}$ " NPT   |
| <b>APPROVALS</b>          | 3mm= UL, C-UL, NYC, VdS<br>5mm= UL, C-UL, FM, NYC, LPCB   |
| <b>TEMPERATURE</b>        | 155°F/68°C - Sprinkler<br>139°F/59°C - Cover Plate,<br>200°F/93°C - Sprinkler<br>165°F/74°C - Cover Plate |
| <b>COVER PLATE FINISH</b> | Chrome, Brushed Chrome, Brass, Signal White, Grey White, Jet Black, Custom                                |
| <b>SIN</b>                | TY3551, TY3531  |
| <b>TECH DATA</b>          | TFP181  |



Sprinkler Wrench



### TY-L

#### Upright, Pendent & Recessed Pendent

- All hazards
- Solder type
- Discharges a hemispherical water spray pattern in the area beneath the sprinkler
- Designed for use in light, ordinary, and extra hazard, commercial occupancies such as banks, hotels, shopping malls, factories, refineries, chemical plants, etc.

|                          |   |
|--------------------------|---|
| <b>K FACTOR</b>          | K=5.6 (80,6)<br>K=8.0 (115,2)   |
| <b>THREAD SIZE</b>       | $\frac{1}{2}$ " NPT • $\frac{3}{4}$ " NPT                                   |
| <b>APPROVALS</b>         | UL, C-UL, FM, LPCB  |
| <b>TEMPERATURE</b>       | 165°F/74°C, 212°F/100°C,<br>280°F/138°C                                     |
| <b>ESCUTCHEON</b>        | Style 20 • Style 30   |
| <b>ESCUTCHEON FINISH</b> | Signal White, Chrome Plated, Brass Plated                                   |
| <b>SPRINKLER FINISH</b>  | Natural Brass, Chrome Plated, Lead Coated, Wax Coated, Wax over Lead Coated |
| <b>SIN</b>               | TY3111, TY3211, TY4111<br>TY4211, TY4811, TY4911                            |
| <b>TECH DATA</b>         | TFP110  |



Sprinkler Wrenches



Always refer to the product's Technical Data Sheet for a complete description of all Listing and Approval criteria, design parameters, installation instructions, care and maintenance guidelines, and our limited warranty.